

# Card holder

## Wiegand RFID holder



Model number:	<b>CH-TR-W-IQ</b>	EM, 125 kHz, white
	<b>CH-TR-B-IQ</b>	EM, 125 kHz, black
	<b>CH-TR-S-IQ</b>	EM, 125 kHz, silver
	<b>CH-TR-I-IQ</b>	EM, 125 kHz, ivory
	<b>CH-TM-W-IQ</b>	Mifare, white
	<b>CH-TM-B-IQ</b>	Mifare, black
	<b>CH-TM-S-IQ</b>	Mifare, silver
	<b>CH-TM-I-IQ</b>	Mifare, ivory
Mounting:	Field, 3M rectangular flush box	
Connection:	Wiegand to <a href="#">Card reader interface</a>	

## Technical specifications

Power supply:	12 VDC
Protection:	IP66
Card interface:	EM 125 kHz, Mifare
Output Interface:	Wiegand 26

From:

<http://wiki.hiq-home.com/> -

Permanent link:

[http://wiki.hiq-home.com/doku.php?id=en:hiq\\_hw:ch-tx&rev=1568285618](http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:ch-tx&rev=1568285618)

Last update: **2019/09/12 10:53**

