

Blinds controller

Wireless blinds controller



Model number:	EN-BC-IW-IQ
Mounting:	In-field; flush box
Dimensions:	40 x 44 x 16.9 mm
Connection:	Wireless EnOcean to MC-230-01

- Auto calibration
- Ultra low profile
- Easy retrofit
- Remote commissioning

Technical specifications

Power supply:	230V AC ~ 50Hz
Switching capabilities:	230V AC - 3A
Consumption:	<1W
Maximum output power:	280 W - 60 Nm
Radio frequency range:	868,0 to 868,6 MHz
RF power max:	+3dBm
Range:	Up to 30m indoor
Wireless repeater:	Yes
Operational temperature:	0°C to 40°
Protection rating:	IP 2X
Pairing:	up to 22 controllers
EEP (EnOcean Profile):	D2-05-00
Dimensions :	40 x 44 x 16.9 mm

Certifications and standards

Europe

- EN 60669-1 : 1999+A1:02+A2:08 - EN 60669-2-1 : 2004+A1 : 09+A12 : 10
- EN301489-01 V2.1.1 - EN301489-03 V2.1.1
- EN300220-2 V3.1.1
- EN62479 : 2010
- 2012/19/EC WEEE Directive
- 2006/95/EC
- 2014/35/EU

From:

<http://wiki.hiq-home.com/> -

Permanent link:

http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:en-bc-iq&rev=1563950431

Last update: **2019/07/24 06:40**

