

Blinds controller

Wireless blinds controller



| | |
|---------------|---------------------------|
| Model number: | BC-WE-F1 |
| Mounting: | In-field; flush box |
| Dimensions: | 40 x 44 x 16.9 mm |
| Connection: | Wireless EnOcean |
| | MC-230-01 |
| | MC-230-03 |
| | MC-24-01 |
| | MC-24-03 |
| | MC-24-05 |

- Auto calibration
- Ultra low profile
- Easy retrofit
- Remote commissioning

Technical specifications

| | |
|--------------------------|----------------------|
| Power supply: | 230V AC ~ 50Hz |
| Switching capabilities: | 230V AC - 3A |
| Consumption: | <1W |
| Maximum output power: | 280 W - 60 Nm |
| Radio frequency range: | 868,0 to 868,6 MHz |
| RF power max: | +3dBm |
| Range: | Up to 30m indoor |
| Wireless repeater: | Yes |
| Operational temperature: | 0°C to 40° |
| Protection rating: | IP 2X |
| Pairing: | up to 22 controllers |
| EEP (EnOcean Profile): | D2-05-00 |
| Dimensions : | 40 x 44 x 16.9 mm |

Certifications and standards

Europe

- EN 60669-1 : 1999+A1:02+A2:08 - EN 60669-2-1 : 2004+A1 : 09+A12 : 10
- EN301489-01 V2.1.1 - EN301489-03 V2.1.1
- EN300220-2 V3.1.1
- EN62479 : 2010
- 2012/19/EC WEEE Directive
- 2006/95/EC
- 2014/35/EU

From:
<http://wiki.hiq-home.com/> -

Permanent link:
http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:en-bc-iq&rev=1589961298

Last update: **2020/05/20 07:54**

