

Relay Switch

Wireless relay switch, 2 channel



Model number:	RS2-WE-F2
Mounting:	In-field; flush box
Dimensions:	40 x 44 x 16.9 mm
Connection:	Wireless EnOcean
	MC-230-01
	MC-230-03
	MC-24-01
	MC-24-03

- High switching capacity
- Ultra low profile
- Potential-free input
- Remote commissioning

Technical specifications

Power supply:	230V AC ~ 50 Hz
Switching capabilities:	230V AC - 2 x 5A
Consumption:	<1W
Maximum output power:	2 x 1150W (resistive load)
Radio frequency range:	868,0 to 868,6 MHz
RF power max:	+3dBm
Range:	Up to 30m indoor
Wireless repeater:	Yes
Operational temperature:	0°C to 40°
Protection rating:	IP 30
Pairing:	up to 22 controllers
EEP (EnOcean Profile):	D2-01-0F
Dimensions :	40 x 44 x 16.9 mm

Certifications and standards

Europe

- EN60669-1:1999+A1:02+A2:08
- EN60669-2-1:2004+A1:09+A12:10
- EN300220-2 V3.1.1
- EN301489-01 V2.1.1
- EN301489-03 V2.1.1
- EN62479:2010

rs2-we-f2_user_manual.pdf

From:

<http://wiki.hiq-home.com/> -

Permanent link:

http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:en-rs2-iq&rev=1591006444

Last update: **2020/06/01 10:14**

