# IOT Linker 2 Ethernet Port

**Advanced EDGE device. Connects Cybro, MC and RDX Charger to HIQ universe**




| | |
|---|---|
| Order code without Power Supply | **IOT-L2-2** |
| Order code with AC Power Supply 230VAC/5VDC | **IOT-L2-2-AC** |
| Order code with DC Power Supply 24VDC/5VDC | **IOT-L2-2-DC** |
| License for specific IOT linker software | **IOT-C2-xx; xx-version of the software** |
| 4G LTE USB modem for IOT linker | **IOT-L2-W** |
| Mounting: | DIN rail, (Optional wall) |
| Dimensions: | 60 x 61 x 26 mm |
| Connection: | LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe |

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

## Technical specifications

| | |
|---|---|
| Power supply: | USB-C, 5V DC |

| | |
|---|---|
| Storage: | MicroSD x1 for external storage up to 128GB |
| USB Host: | 1x 2.0 Type-A |
| Network: | 2x 10/100/1000M Ethernet |
| Working temp.: | 0℃ to 80℃ |
| 4G connection : | USB |
| Software : | IOT linker system software is sold separately on MicroSD card |

# Mounting

### DIN Rail, Optional Wall







From:
https://wiki.hiq-home.com/ -

Permanent link:
**https://wiki.hiq-home.com/doku.php?id=en:hiq_hw:iot_linker**

Last update: **2023/01/28 21:15**