

# IOT Linker 2 Ethernet Port

**Advanced EDGE device. Connects Cybro, MC and RDX Charger to HIQ universe**



Order code without Power Supply	<b>IOT-L2-2</b>
Order code with AC Power Supply 230VAC/5VDC	<b>IOT-L2-2-AC</b>
Order code with DC Power Supply 24VDC/5VDC	<b>IOT-L2-2-DC</b>
License for specific IOT linker software	<b>IOT-C2-xx; xx-version of the software</b>
4G LTE USB modem for IOT linker	<b>IOT-L2-W</b>
Mounting:	DIN rail, (Optional wall)
Dimensions:	60 x 61 x 26 mm
Connection:	LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

# Technical specifications

Power supply:	USB-C, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0°C to 80°C
4G connection :	USB
Software :	IOT linker system software is sold separately on MicroSD card

## Mounting

### DIN Rail, Optional Wall



From: <https://wiki.hiq-home.com/> -

Permanent link: [https://wiki.hiq-home.com/doku.php?id=en:hiq\\_hw:iot\\_linker](https://wiki.hiq-home.com/doku.php?id=en:hiq_hw:iot_linker)

Last update: **2023/01/28 21:15**

