Master Controller

Advanced Controller



Model number:	**MC-24-01**	24 VAC, 11 IO, Enocean, 2 × RS232, RS485, IEX2 terminals
	MC-24-02	24 VAC, 11 IO, 2 × RS232, RS485, IEX2 terminals
	MC-24-03	24 VAC, 11 IO, Enocean, 2 × RS232, isolated RS485, IEX2 terminals
	MC-24-04	24 VAC, 11 IO, 2 × RS232, isolated RS485, IEX2 terminals
Mounting:	DIN rail, 6M, 106mm	
Dimensions:	106x108x58mm	

Features

- 3 digital inputs
- 4 relay outputs 8 A
- 4 universal inputs/outputs
- Ethernet, USM, IEX-2, 2×RS232, 1×RS485 (optional isolated)
- Enocean gateway (optional)
- 24 VDC power supply

Safety standards

EN 50081-1, EN 61000-6-2, EN 61131-1, EN 61131-2, EN 61000-3-2, EN 61000-3-3

Technical specification

Relay outputs:	8A/250V
Communication:	Ethernet, 2x RS232, 1x RS485, IEX-2 bus
Nominal power rating:	24 VDC
Power consumption:	typ. 1W (no load), 10W max
Ingress protection:	IP20
Operating temperature:	0..45°C
Storage temperature:	-20..75°C
Relative humidity:	0..95% n/c

Terminals

From:
https://wiki.hiq-home.com/ -

Permanent link:
https://wiki.hiq-home.com/doku.php?id=en:hiq_hw:mc-24&rev=1566215527

Last update: **2019/08/19 11:52**