

Master Controller

Advanced Controller



| | | |
|---------------|---------------------|---|
| Model number: | MC-24-01 | 24 VAC, 11 IO, Enocan, 2 × RS232, RS485, IEX2 terminals |
| | MC-24-02 | 24 VAC, 11 IO, 2 × RS232, RS485, IEX2 terminals |
| Mounting: | DIN rail, 6M, 106mm | |
| Dimensions: | 106x108x58mm | |

Features

- 12 digital inputs
- 10 relay outputs 8 A
- 4 universal inputs/outputs
- Ethernet, USM, IEX-2, 2×RS232
- Enocan gateway (optional)
- 24 VDC power supply

Safety standards

EN 50081-1, EN 61000-6-2, EN 61131-1, EN 61131-2, EN 61000-3-2, EN 61000-3-3

Technical specification

| | |
|------------------------|---|
| Relay outputs: | 8A/250V |
| Communication: | Ethernet, 2x RS232, 1x RS485, IEX-2 bus |
| Nominal power rating: | 24 VDC |
| Power consumption: | typ. 1W (no load), 10W max |
| Ingress protection: | IP20 |
| Operating temperature: | 0..45°C |
| Storage temperature: | -20..75°C |
| Relative humidity: | 0..95% n/c |

Terminals

From:
<http://wiki.hiq-home.com/> -

Permanent link:
http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:mc3-24&rev=1566215504

Last update: **2019/08/19 11:51**

