

RDX Charger (Robotina Dynamic Charger)



Description	Order Code
RDX Charger with type 2 cable and RFID card reader	RDX-RF
RDX Charger with type 2 cable, RFID reader and RCD AC	RDX-RF-R
RDX Charger with type 2 cable, RFID reader and IOT Linker	RDX-RF-I
RDX Charger with type 2 cable, RFID reader, RCD AC and IOT linker	RDX-RF-RI
RDX Charger with type 2 cable and QR code reader	RDX-QR
RDX Charger with type 2 cable, QR code reader and RCD AC	RDX-QR-R
RDX Charger with type 2 cable, QR code reader and IOT Linker	RDX-QR-I
RDX Charger with type 2 cable, QR code reader, RCD AC and IOT linker	RDX-QR-RI

Features


- Up to 22kW of charging power
- Modern design with IP54 & IK10 standard
- Suitable for indoor and outdoor use
- Coloured LED light indicates charging status
- Easy operability with one button on housing
- Monitor & control on application
- Compatible with 3rd party software
- Secure charger with remote locking option
- Save by charging (economy charging) during off-peak hours
- Charge with surplus energy

- **Priority charging at the highest possible power**
- **Dynamic load balancing keeps consumption power below max allowed (protect grid fuse/s)**
- **Manage charging of electric vehicles (EV fleet)**
- **Remote control of key consumers (heat pump, battery storage system...)**
- **6mA DC residual current, overvoltage and undervoltage protection**
- **30mA AC residual current**
- **RFID or QR access control**
- **Long range wireless power meters for installation without cabling**
- **Fully compliant with IEC 61851**

Technical specifications

Nominal voltage	1x230Vac 50/60Hz, 3x230/400Vac 50/60Hz
Maximum current	1x32A, 3x32A
Maximum charging power	22kW
Connector	Type2, 5m cable
Network connection	Ethernet 100M RJ45
Ingress protection	IP54
Impact resistance	IK10
Operating temperature	-20°C to +60°C
Storage temperature	-40°C to + 70°C
RCD AC (optional)	30mA
RDC DC	6mA
Standards	IEC 61851

Dimensions



Cable holder mounting options

It can be installed directly on the RDX Charger



It can be installed independently on the wall



Accessories

Description	Order Code
Wireless external single-phase Power sensor kit	WPM1-E-D
Wireless external three-phase Power sensor kit	WPM3-E-D
External single-phase Power sensor	PM1-E-D
External three-phase Power sensor	PM3-E-D
Wireless Modbus bridge	WM-1
Wireless relay, to control other loads in the building	WR-1
Protective roof	RDX-PR
Freestanding set	RDX-FS
4G LTE modem for IOT linker This option is only possible for RDX Charger models that already have an integrated IOT linker	IOT-L2-W

From:

<http://wiki.hiq-home.com/> -

Permanent link:

http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:rdx_charger&rev=1674558690

Last update: **2023/01/24 11:11**

