


# Touch keypad

## Wiegand Touch keypad and RFID receiver



Model number:	<b>TK-FR-B</b>	Touch keypad, RFID card reader EM 125 kHz, black
Mounting:	Field, on wall	
Connection:	Wiegand to <a href="#">Card reader interface</a>	

## Technical specifications

Power supply:	9-15 VDC / 200mA
Reading Distance:	3-6 cm
Card interface:	EM 125 kHz
Output Interface:	Wiegand 26
Dimensions:	62 x 23 x 142 mm

## Wiring

CR-MR	CR-W2-IQ		MC-230-3W		Notes
	1st	2nd	1st	2nd	
RD	+12V		+12V		Power supply
BK	GND		GND		
BU	-		-		Not connected
GN	D0-0+1		D0		Wiegand data
WH	D1-0	D1-1	D1-0	D1-1	
BN	GN-0	GN-1	GN-0	GN-1	LED indicator
YE	-		-		Not connected
VT	-		-		Not connected

From:

<http://wiki.hiq-home.com/> -

Permanent link:

[http://wiki.hiq-home.com/doku.php?id=en:hiq\\_hw:touch\\_keypad&rev=1586250475](http://wiki.hiq-home.com/doku.php?id=en:hiq_hw:touch_keypad&rev=1586250475)

Last update: **2020/04/07 09:07**

