


# Hotel room controller

## Hotel room master controller



|               |                     |
|---------------|---------------------|
| Model number: | <b>HR-2</b>         |
| Mounting:     | DIN rail, 6M, 106mm |
| Dimensions:   | 106x108x58mm        |

## Applications

- Hotel room automation

## Features

- Welcome light
- Power relay
- HVAC control
- Room SOS

## General description

**Hotel room controller** controls all basic hotel room devices: welcome light, power relay, HVAC, card holder and SOS pull-switch. By itself is sufficient for basic hotel room automation. It is easy configurable and can be upgraded with many additional expansion units so it ensures practically any level of hotel room automation.

Easy commissioning with auto-addressing, easy configuration and advanced diagnostic ensures cost effective and quick system set-up and easy maintenance during whole life cycle.

## Technical specification

|                |             |
|----------------|-------------|
| Relay outputs: | 3A/250V     |
| Lock output:   | 500mA/12VDC |

|                        |                    |
|------------------------|--------------------|
| Transistor outputs:    | 250mA/24VDC        |
| Communication:         | RS485, 2 × IEX bus |
| Power supply:          | 240V               |
| Ingress protection:    | IP20               |
| Operating temperature: | 0..45°C            |
| Storage temperature:   | -20..75°C          |
| Relative humidity:     | 0..95% n/c         |

## Terminals

|                           |              |           |                    |                       |           |             |                                |                                   |
|---------------------------|--------------|-----------|--------------------|-----------------------|-----------|-------------|--------------------------------|-----------------------------------|
| Power supply 240 V AC     | <b>L</b>     | <b>1</b>  | Power supply input | Digital inputs common | <b>19</b> | <b>GND</b>  | Common                         |                                   |
|                           | <b>N</b>     | <b>2</b>  |                    | Digital inputs        | <b>20</b> | <b>IX0</b>  | Card holder                    |                                   |
| Room power relay          | <b>PWR</b>   | <b>3</b>  | Relay outputs      | Digital inputs        | <b>21</b> | <b>IX1</b>  | Thermostat                     |                                   |
| Fan-coil 1st speed        | <b>F1</b>    | <b>4</b>  |                    | Digital inputs        | <b>22</b> | <b>IX2</b>  | Main door reed relay           |                                   |
| Fan-coil 2nd speed        | <b>F2</b>    | <b>5</b>  |                    | Digital inputs        | <b>23</b> | <b>IX3</b>  | Welcome light push-button      |                                   |
| Fan-coil 3rd speed        | <b>F3</b>    | <b>6</b>  |                    | Digital inputs        | <b>24</b> | <b>IX4</b>  | SOS pull-switch                |                                   |
| Fan-coil valve            | <b>VA</b>    | <b>7</b>  |                    | Digital inputs        | <b>25</b> | <b>IX5</b>  | Info panel control push-button |                                   |
| Welcome light             | <b>QX0</b>   | <b>8</b>  |                    | Digital inputs        | <b>26</b> | <b>IX6</b>  | Window switch                  |                                   |
| Thermostat ECO mode       | <b>QX1</b>   | <b>9</b>  |                    | Digital inputs        | <b>27</b> | <b>IX7</b>  |                                |                                   |
| Internal IEX bus GND      | <b>GND</b>   | <b>10</b> | Internal IEX bus   | +12 VDC source        | <b>28</b> | <b>+12V</b> | Access control +12V            |                                   |
| Internal IEX bus CANL     | <b>ICANL</b> | <b>11</b> |                    | RS485                 | <b>29</b> | <b>A</b>    | Access control RXD-A           |                                   |
| Internal IEX bus CANH     | <b>ICANH</b> | <b>12</b> |                    | RS485                 | <b>30</b> | <b>B</b>    | Access control TXD-B           |                                   |
| Internal IEX bus +24V     | <b>+24V</b>  | <b>13</b> | External IEX bus   | GND                   | <b>31</b> | <b>GND</b>  | Access control GND             |                                   |
| External IEX bus GND      | <b>GND</b>   | <b>14</b> |                    | GND                   | <b>32</b> | <b>GND</b>  | LOCK and Qx2-4 common          |                                   |
| External IEX bus CANL     | <b>ECANL</b> | <b>15</b> |                    | Lock output           | <b>33</b> | <b>LOCK</b> | Door lock                      |                                   |
| External IEX bus CANH     | <b>ECANH</b> | <b>16</b> |                    | Transistor outputs    |           | <b>34</b>   | <b>QX2</b>                     | Info panel - Make My Room         |
| External IEX bus in +24V  | <b>+IN</b>   | <b>17</b> |                    |                       |           | <b>35</b>   | <b>QX3</b>                     | Info panel - Do Not Disturb       |
| External IEX bus out +24V | <b>+OUT</b>  | <b>18</b> |                    |                       |           | <b>36</b>   | <b>QX4</b>                     | Info panel - Room Service Request |

From: <http://wiki.hiq-home.com/> -

Permanent link: <http://wiki.hiq-home.com/doku.php?id=en:hotel:hardware:hr-2-iq&rev=1542873841>

Last update: 2018/11/22 08:04

