

IOT Linker 2 Ethernet Port

connected home for future connected services



| | |
|--|---|
| Order code (without Power Supply): | IOT-L2-2 |
| Order code (with AC Power Supply 230VAC/5VDC): | IOT-L2-2-AC |
| Order code (with DC Power Supply 24VDC/5VDC): | IOT-L2-2-DC |
| Mounting: | DIN rail, wall |
| Dimensions: | 60 x 61 x 26 mm |
| Connection: | Ethernet Port 1: connects to Cybro Ethernet Port 2: uplink to HIQ Universe |

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ MC controllers

Technical specifications

| | |
|-----------------|---|
| Power supply: | Micro USB, 5V DC |
| Storage: | MicroSD x1 for external storage up to 128GB |
| USB Host: | 1x 2.0 Type-A |
| Network: | 2x 10/100/1000M Ethernet |
| Working temp.: | 0°C to 40°C |
| 4G connection : | USB |
| Software : | IOT linker system software is sold separately on MicroSD card |

Mounting

DIN Rail or Wall



From:
<https://wiki.hiq-home.com/> -

Permanent link:
https://wiki.hiq-home.com/doku.php?id=iot_linker&rev=1606305896

Last update: **2020/11/25 12:04**

