

# IOT Linker 2 Ethernet Port

connected home for future connected services



|  |   |
|--|---|
| Order code (without Power Supply):             | <b>IOT-L2-2</b>   |
| Order code (with AC Power Supply 230VAC/5VDC): | <b>IOT-L2-2-AC</b>  |
| Order code (with DC Power Supply 24VDC/5VDC):  | <b>IOT-L2-2-DC</b>  |
| Mounting:                                      | DIN rail, wall  |
| Dimensions:                                    | 60 x 61 x 26 mm   |
| Connection:                                    | Ethernet Port 1:<br>connects to Cybro<br>Ethernet Port 2: uplink<br>to HIQ Universe |

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ MC controllers

## Technical specifications

|                 |   |
|-----------------|---|
| Power supply:   | Micro USB, 5V DC  |
| Storage:        | MicroSD x1 for external storage up to 128GB                   |
| USB Host:       | 1x 2.0 Type-A   |
| Network:        | 2x 10/100/1000M Ethernet                                      |
| Working temp.:  | 0°C to 40°C   |
| 4G connection : | USB   |
| Software :      | IOT linker system software is sold separately on MicroSD card |

## Mounting

### DIN Rail or Wall



From:  
<http://wiki.hiq-home.com/> -

Permanent link:  
[http://wiki.hiq-home.com/doku.php?id=iot\\_linker&rev=1606305896](http://wiki.hiq-home.com/doku.php?id=iot_linker&rev=1606305896)

Last update: **2020/11/25 12:04**

