



Questa pagina non è ancora completamente tradotta. Chi può potrebbe aiutarne il completamento.

(Rimuovere questo paragrafo a lavoro completato)

Dispositivi controllabili con HIQ

Luci

Che tipo di luci posso controllare?

- Normali (On/Off)
- Normali dimmerabili
- Dimmerabili con DALI
- Dimmerabili strisce a LED
- Dimmerabili strisce a LED RGB

Come sono controllabili * Tramite pulsante locale e/o rilevatore di presenza * Tramite scenari pre-programmati * Tramite telecomando IR * Tramite applicazioni HIQ Perché controllare le luci con HIQ? * **Semplicità di utilizzo * Modo/i temporizzati * Controllo di più luci con scenari preimpostati * Semplice visualizzazione con HIQ commander**



^ Controlled device ^ Devices/controller
 ^ Devices/module ^ Control module ^
 Modules/controller ^ | Light - General purpose On/Off | 40 | **10** | **LC-10-IQ** | **4**
 | | **Light - 230 VAC dimmable** | 16 | **4**
 | **LD-P4-IQ** | **4** | | **Light - DALI light** |
 ::: | **8** | **LD-D8-IQ** | **2** | | **Light - single color LED stripe** | ::: | **4** | **LD-V4-IQ** |
4 | | **Light - RGB(W) LED stripe** | **4** | **1**
 | ::: | ::: |

===== Blinds =====

Which type of blinds can we control?



- Blinds
- Curtains
- Awnings
- Shades
- Projector screen and lift

Basically all type of bidirectional motorized blinds with built-in limit switches.

How blinds are controlled

- Local auto up/down push-button (same function as automatic car windows)
- Through scene
- With IR remote controller
- From HIQ applications

Why control blinds with HIQ?

- Easy local control

(just
press
button -
no need
to hold
and wait)

- Control
many
blinds
with one
click with
scenes
- Easy
overview
and
control
with HIQ
command
er

^ Controlled device ^ Devices/controller
^ Devices/module ^ Control module ^
Modules/controller ^ | Blinds, shadings,
curtains, awnings | 10 | 5 | **BC-5-IQ** | 2 |

===== Managed power sockets

=====

Individually controlled sockets for:



- Table lights
- Standing lights
- Standing fans
- Christmas tree lights
- Small home appliances (coffee machine, kettle, ...)
- Boiler
- Domestic water heater
- Washing machine
- Dryer

Group controlled general sockets:

- To switch off all sockets during night and when not at home
- Do not use for appliances which constantly in need power supply for undisturb

ed
operation
(refrigerat
or,
freezer,
...):

How managed sockets are controlled?

- Locally with push-buttons
- Through scene
- With IR remote controller
- From HIQ applications

Why control sockets with HIQ?


- Easy local control
- Timer mode
- Control many sockets with one click with scenes
- Easy overview and control with HIQ commander
- Automatically power off dangerous appliances like iron

or cooker
when you
are away

^ Controlled device ^ Devices/controller
^ Devices/module ^ Control module ^
Modules/controller ^ | Power socket | 40
| **10** | **LC-10-IQ** * | **4** | * **external**
power relay is highly recommended

===== Exhaust fans =====

All single speed exhaust fans in toilets, kitchen, garage, ...



How exhaust fans are controlled?

- Locally with push-buttons
- Through scene
- With IR remote controller
- From HIQ applications

Why control exhaust fans with HIQ?

- Easy local control
- Timer mode
- Control many fans with one click with scenes
- Easy overview and control with HIQ commander

^ Controlled device ^ Devices/controller
 ^ Devices/module ^ Control module ^
 Modules/controller ^ | Exhaust fan | 40 |
10 | LC-10-IQ | 4 |

===== Scenes =====

Scene sets a group of lights, shades (curtains), fans and managed sockets to the present value.



Scene can be set with:

- Local push-button with LED indicator which indicate if scene is active
- With IR remote controller
- From HIQ applications

Affected devices are simple selected in PC GUI application.

User can easy store actual state of all affected lights and position of affected blinds into scene by long-press scene button.

^ Controlled device ^ Devices/controller
^ Devices/module ^ Control module ^
Modules/controller ^ | Scene push-button with LED indicator | 16 | **4** |

SC-4S-IQ | 4 | | Scene touch panel |
::: | / | SC-4T-IQ | ::: |

==== HVAC ==== Multi zone temperature control maintain optimum temperature each room, depending on the purpose and the actual needs. HiQ supports multiple schedules for heating / cooling and advanced energy efficiency algorithms.

Supported devices:

- Heating/cooling source
 - Boiler
 - Chiller
 - Heat pump
- Heating/cooling elements
 - Fan-coils (Convectors)
 - Radiators
 - Surface heating and cooling (floor, ceiling or wall)



- Air-
con
diti
one
rs
(ON
/OF
F)
- Do
mes
tic
wat
er
hea
ting

How HVAC devices are controlled?

- Locally
with
thermosta
t
- From HIQ
applicatio
ns

Features:

- Easy local
setpoint
correction
- Advanced
fan-coil
functions:
 - tim
e
limi
ted
MA
X
mo
de
 - fan
spe
ed
limi
tati
on
- 3 setpoint
timetable

S

- set
acti
ve
setp
oint
- Hi / Low
limits for
setpoint
- Easy
configurat
ion with
PC GUI
- Automatic
ally
disable
heating /
cooling
when
window is
open or
condensat
ion point
is reached
(in cooling
mode)

```

^ Controlled device ^ Devices/controller
^ Devices/module ^ Control module ^
Modules/controller ^ | HVAC - Zone
thermostat | 5 | / | TH-1M-IQ | 5 | | :: |
:: | :: | TH-1T-IQ | :: | | :: | :: | :: |
TH-2-IQ | :: | | :: | :: | :: | TH-3-IQ |
:: | | HVAC - Fan-coil | 5 | 1 | FC-1-IQ
| 5 | | HVAC - Radiator valve | 5 | 5 |
HC-IQ | 1 | | HVAC - Floor heating
valve | :: | :: | :: | :: | | HVAC -
Ceiling cooling valve | :: | :: | :: |
:: | | HVAC - Boiler (On/Off) | 1 | 1 |
:: | :: | | HVAC - Chiller (On/Off) | 1 |
1 | :: | :: | ===== Access control
=====

```

Supported devices:



- Unlock your door using smartphone and HIQ Commander



- Intercoms (IP and analog, voice and/or video versions)
- Fingerprint readers
- RFID readers
- GSM modem

How access control devices are controlled?

- Locally with push-buttons (on the

- inner wall)
- From HIQ applications
- From access control device

Why link your access control device with HIQ?

- Open your door with HIQ applications
- Add remote function
- Unique identification creates the ideal conditions for a HIQ home system that works as efficiently as possible so that your house knows who is at home
- Access control monitoring

===== Safety & security =====

Supported devices:

- Motion sensors
- Door/window sensors
- Gas sensors (CH₄, LPG)
- Smoke detectors
- Water leak detectors
- Air quality sensors
- Various gas detection (CO₂, CO, NO₂, O₂...)
- Condensation sensors
- GSM modem



Alarm transmission:

- Indication with a horn/light (or a scene) which is linked to an appropriate output.
- Connection with home alarm.
- The appropriate output

can be connected to actuator which closes the water / gas in the whole house/apartment.

- Switch off cooling when condensation occurs.
- Connection with ventilation/recuperation system.
- Connection with [GSM modem](#) that sends SMS and/or make a telephone call.

From:
<http://wiki.hiq-home.com/> -

Permanent link:
http://wiki.hiq-home.com/doku.php?id=it:hiq_building_automation:hiq_home:general:devices&rev=1537432964

Last update: **2018/09/20 08:42**

