

HiQ introduzione I dispositivi (ad esempio: luci o tapparelle) e le interfacce utente di base (come pulsanti) e sensori (come l'illuminamento o i sensori di temperatura) sono collegati a HiQ-DC. Funzionalità di base (pulsante è la luce di commutazione) è implementato direttamente su HiQ-DC, al fine di essere reattivo, in quanto è affidabile e indipendente dalle infrastrutture di comunicazione, come bus di controllo, rete domestica e connessione Internet.

HIQ Home Selection table

Controllers

Name	Code	Description	Mounting
HIQ Controller			
HIQ controller	HC-IQ	Advanced HIQ controller	Cabinet; DIN rail 6M
Device Controllers			
Light controller	LC-10-IQ	10 relay-controlled outputs	Cabinet; DIN rail 6M
LED stripe dimmer	LD-V4-IQ	4 channel 12/24 V constant voltage LED dimmer	In-field; flush box or dry-wall
Light dimmers driver	LD-P4-IQ	4 channel driver for universal light dimmers	Cabinet; DIN rail 2M
DALI dimmer	LD-D8-IQ	8 DALI groups dimmer	Cabinet; DIN rail 2M
Blinds controller	BC-5-IQ	5 blinds position controller	Cabinet; DIN rail 6M
Scene panel	SC-40-IQ	4 scene controller with IR receiver	In-field; 3M rectangular flush box
Scene touch panel	SC-4T-IQ	4 scene controller with IR receiver	In-field; 3M rectangular flush box
Scene controller	SC-4S-IQ	4 scene controller using various push buttons	In-field; flush box behind buttons
Thermostat	TH-1M-IQ	Electronic thermostat	In-field; 3M rectangular flush box
	TH-1T-IQ	Touch electronic thermostat	In-field; 3M rectangular flush box
	TH-2-IQ	Blind electronic thermostat	In-field; on-wall
Thermostat & scene controller	TH-3-IQ	Electronic thermostat and scene controller	In-field; on-wall
HVAC controller	FC-1-IQ	3 speed fan and valves controller	In-field; fan-coil, flush box or dry-wall

System accessories

Name	Code	Description	Mounting
Power supply	PS-IQ	24 VDC / 3.8 A power supply	Cabinet; DIN rail 5M
Power meter set	PM-1-IQ	single phase direct connection power meter set	Cabinet; DIN rail 1+2M
3-ph Power meter set	PM-3-IQ	3-phase direct connection power meter set	Cabinet; DIN rail 4+2M
PIR sensor	IR-580-IQ	Indoor PIR motion sensor	In-field; on-wall
Door switch	REED-SW	Door / window switch	door / window frame

Lightness sensor	RHKF-U	Outside and indoor lightness sensor	In-field; on-wall
Remote controller	RE-2-IQ	Flat IR remote controller	Handheld
Light driver	LUD12-IQ	Universal 230 VAC light driver	Cabinet; DIN rail 1M
Buttons	CAD-2-BUT-IQ	2 mini buttons	Cabinet; On module
Push button illumination	CAD-SW-LED-IQ	white LED illumination	In-field, flush box in buttons
Bus extender	CAD-BE-PROT-IQ	RJ9 to wires bus adapter, surge protection	Cabinet; DIN rail 2M
Bus cable	CAD-P-IQ	2.5 cm RJ9 to RJ9 bus cable	Cabinet; module to module, 2.5cm
	CAD-P2-IQ	2 m RJ9 to RJ9 bus cable	Cabinet; module to module, 2m
Temperature sensor	ES-IQ	External temperature sensor	In-field
	ES-A-IQ	External temperature sensor in Aluminum housing	In-field

Training and Demo material

Name	Code	Description
Demo suitcase	HIQ-MOB-ST-KIT	Mobile demonstration set
Demo suitcase and set	HIQ-MOB-EX-KIT	Mobile demonstration set + start set
Demo wall	HIQ-WALL-KIT	"Window to future" multimedia set

Stylish accessories



Name	Code	Description
------	------	-------------

Decorative frame	OL30ES	Elox silver line plastic for 3 M
	OL40ES	Elox silver line plastic for 4 M
	OS30ES	Elox silver soft plastic for 3 M
	OS40ES	Elox silver soft plastic for 4 M
	OS30SB	Black soft plastic for 3 M
	OS40SB	Black soft plastic for 4 M
	OP30MH	Hammered steel metal for 3 M
	OP40MH	Hammered steel metal for 4 M
	OP30MS	Satin silver metal for 3 M
	OP40MS	Satin silver metal for 4 M
	OP30WB	Bamboo wood for 3 M
	OP40WB	Bamboo wood for 4 M
	OP30WM	Maple wood for 3 M
	OP40WM	Maple wood for 4 M
	OP30WE	Wenge wood for 3 M
	OP40WE	Wenge wood for 4 M
	OP30GW	Ice white glass for 3 M
	OP40GW	Ice white glass for 4 M
OP30GY	Ice grey glass for 3 M	
OP40GY	Ice grey glass for 4 M	
Push button, 1 way	SM11PW	Polar white
	SM11SB	Soft touch black
	SM11ES	Elox silver
	SM11IW	Ivory
Push button, 1 way, indicator	SM11PWIN	Polar white
	SM11SBIN	Soft touch black
	SM11ESIN	Elox silver
	SM11IWIN	Ivory
Push button, up/down	SM41PWNT10	Polar white
	SM41SBNT10	Soft touch black
	SM41ESNT10	Elox silver
	SM41IWNT10	Ivory
Fixing frame	NM30	3M
	NM40	4M
Flush box	DM30	3M for brick wall
	DM40	4M for brick wall
	HM30	3M for hollow wall
	HM40	4M for hollow wall
	BM30	3M for concrete wall
	BM40	4M for concrete wall

[tem_-_general_catalogue_2016_si.pdf](#)

Custom accessories

Name	Code	Description	Mounting
Audio multi-room system			
Zone player	MRA-ZP	Multi Room Audio Player	Desktop
Ceiling speaker	MRA-SPK-C	Ceiling speaker	Ceiling
Media Server	MRA-MS	Multi Room Audio media server	Desktop
Access control			
Door-phone	AC-DP	TCP/IP video door phone	Outside in-wall
Desktop intercom	AC-DI	Desktop video intercom station	Desktop
Wall intercom	AC-WI	Indoor in-wall mountable intercom	In-wall mountable
GSM SA modem	GSM-SA	GSM StandAlone module	Cabinet; DIN rail 2M
GSM modem	GSM-1	GSM programmable module	Cabinet; DIN rail 2M
Various sensors			
Wind Speed Sensor	FST200-201A	Auto-heated Wind Speed Sensor	Outside
Temperature Sensor	PT1000-O	Outdoor Pt1000 temperature sensor	Outside
Presence sensor	LRM8114-IW	Ceiling mount presence sensor	In ceiling
	LRM8114-OW	Wall mount presence sensor	On wall
EnOcean			
EnOcean gateway	GW-ENO-IQ	EnOcean wireless messages receiver	DB, DIN Rail
IR Blasters			
IR blaster	IR-712A-CR-IQ	2 ch IR blaster	DB, DIN Rail
	IR-210-CR-IQ	6 ch IR blaster	DB, DIN Rail
IR emitter	CA-IR-SH2251-IQ	IR emitter	On wall

From:
<http://wiki.hiq-home.com/> -

Permanent link:
http://wiki.hiq-home.com/doku.php?id=it:hiq_building_automation:hiq_home:hw:hardware&rev=1537430291

Last update: **2018/09/20 07:58**

