

RDX Charger



| Description | Order Code |
|--|------------------|
| Robotina charger with type 2 cable and RFID card reader | RDX-RF |
| Robotina charger with type 2 cable, RFID card reader and residual current device | RDX-RF-R |
| Robotina charger with type 2 cable, RFID card reader and IOT Linker | RDX-RF-I |
| Robotina charger with type 2 cable, RFID card reader, residual current device and IOT linker | RDX-RF-RI |
| Robotina charger with type 2 cable and QR code reader | RDX-QR |
| Robotina charger with type 2 cable, QR code reader and residual current device | RDX-QR-R |
| Robotina charger with type 2 cable, QR code reader and IOT Linker | RDX-QR-I |
| Robotina charger with type 2 cable, QR code reader, residual current device and IOT linker | RDX-QR-RI |

- **Up to 22kW of charging power**
- **Modern design with IP45 & IK10 standard**
- **Suitable for indoor and outdoor use**
- **Coloured LED light indicates charging status**
- **Easy operability with one button on housing for charging modes & stop**
- **Monitor & control charger operation via web-based cloud interface**
- **Compatible with 3rd party software**
- **Secure charger with remote locking option**
- **Save by charging (economy charging) during off-peak hours**
- **Charge with surplus energy (solar & wind energy)**
- **Priority charging at the highest possible power**
- **Dynamic load balancing keeps consumption power below max allowed (protect grid fuse/s)**
- **Manage charging of electric vehicles (EV fleet)**
- **Remote control of key consumers (heat pump, battery storage system,)**
- **6mA DC residual current, overvoltage and undervoltage protection**
- **RFID or QR access control to allow authorized usage only**
- **Long range wireless power meters for installation without cabling**
- **Fully compliant with IEC 61851**

RDX Charger Introduction

PLUG IN & GO


Simply connect vehicle to charge and unplug to drive.

Robotina Charger makes charging as easy as possible by enabling of charging using button on housing or by application on cloud.

BUTTON & LED on housing

- charging starts automatically as soon as vehicle is connected with power cable
- press button to stop charging, press again to restart
- press and hold button to activate priority charging
- LED light indicates charging status
- operating with button doesn't require active application

**Button on housing and "button" on cloud application share same functionality. It doesn't matter which one is used.*



RFID or QR

- authentication for users
- charging starts after authentication is successful
- RFID or QR reader could be installed on housing, both is not possible.

LOCKED

- disable unauthorized use of charging station
- locked is deactivated by authorized RFID card, key fob or by cloud application

ECONOMY CHARGING










- allows charging with a current set by user
- charging at low tariff only (depending on table set by user)
- charging by surplus energy only or in combination with grid power

PRIORITY CHARGING

- Utilize all available power to charge as fast as possible
- In case of *Dynamic load balancing* temporary suspends high-power loads to increase available power for charging simultaneously keeping total power below max allowed power

How to physically mount charger please see [LINK](#) (to be inserted).


How to operate with charger please see [LINK](#) (to be inserted)

| LED indicator | Steady light | Flashing light |
|---|------------------------------|---|
|  | EV not connected | Paused by EVSE (short press to unpause) |
|  | EV connected, not charging | Paused by EVSE (short press to unpause) |
|  | EV connected, charging | / |
|  | EV connected, charging ended | / |
|  | / | Error |
|  | / | Locked |
|  | / | Priority charging |
|  | / | Priority charging paused |
|  | / | Priority charging ended |

Technical specifications

| | |
|-------------------------|--|
| Nominal voltage | 1x230Vac 50/60Hz, 3x230/400Vac 50/60Hz |
| Maximum current | 1x32A, 3x32A |
| Maximum charging power | 22kW |
| Connector | Type2, 5m cable |
| Network connection | Ethernet 100M RJ45 |
| Ingress protection | IP54 |
| Impact resistance | IK10 |
| Operating temperature | -20°C to +45°C |
| Storage temperature | -40°C to + 70°C |
| Charging pilot negative | 1mA, 20ms reaction time |
| Residual direct current | 6mA, 200ms reaction time |
| Standards | IEC 61851 |

Dimensions



Cable holder mounting options

It can be mounted directly on the charger,



or it can be mounted independently on the wall



Accessories

| Description | Order Code |
|--|------------|
| Wireless external single-phase Power sensor | WPM1-E-D |
| Wireless external three-phase Power sensor | WPM3-E-D |
| Wireless relay, to control other loads in the building | WR-1 |
| Protective roof | RDX-PR |
| Freestanding set | RDX-FS |

From:

<http://wiki.hiq-home.com/> -

Permanent link:

http://wiki.hiq-home.com/doku.php?id=rdx_charger&rev=1671195895

Last update:

2022/12/16 13:04

