

TVOC, Temperature and Humidity Sensor



Model number:	RB-100-TVOC-TH
Mounting:	In-wall, dose
Dimensions:	85 x 116 x 44 mm
Connection:	RS485 to HIQ MC controller or Cybro
Frame color:	Black

Applications

- HVAC and indoor air monitoring
- Widely used in building automation
- Climate, ECO2 and HVAC signal collection

Features

- High measurement accuracy
- Built-in high-performance microprocessor
- Multiple probes available
- Superior performance and long-term stability

Technical specifications

Power supply:	10-30VDC Note: 0-10VDC output (limited to 24VDC Power Supply)
Signal output:	4-20mA/0-5VDC/0-10VDC RS485 output (Modbus protocol)
Digital output:	Device address 1-255, default 1

Last update: 2022/11/29 12:27 tvoc_temperature_and_humidity_sensor http://wiki.hiq-home.com/doku.php?id=tvoc_temperature_and_humidity_sensor&rev=1669724831

	Device baud rate 2400, 4800, 9600 optional, default 4800
	Byte format 8-bit data bit, 1 stop bit, no parity
Measuring temperature	-40°C to +80°C
Measuring humidity :	Relative humidity 0%-100% RH
Temperature accuracy :	0.5°C (25°C)
Humidity accuracy :	3% RH (5%RH-95%RH, 25°C)
Long-term stability :	Temperature < 0.1°C/year, Humidity <0.1%RH/year
Response time :	Temperature <18sec (1m/s wind speed), Humidity < 6sec (1m/s wind speed)

From:
<http://wiki.hiq-home.com/> -

Permanent link:
http://wiki.hiq-home.com/doku.php?id=tvoc_temperature_and_humidity_sensor&rev=1669724831

Last update: **2022/11/29 12:27**

